

# Respirator Fit Testing Checklist



Under OHS regulations, workers required to use respirators with tight-fitting facepieces must undergo fit testing to ensure a proper fit and prevent leakage. Use this Checklist to determine if you comply with OHS requirements and remain in compliance going forward.

## CHECKLIST FOR RESPIRATOR FIT TESTING

û Check all the fit tests listed below that are used at your facility or workplace:

- ☐ Employees who are using tight-fitting respirator facepieces have passed an appropriate fit test before being required to use a respirator.
- ☐ Fit testing is conducted with the same make, model, style and size that the employee will be expected to use at the worksite.
- ☐ Fit tests are conducted annually and when different respirator facepieces are to be used.
- ☐ Provisions are made to conduct additional fit tests in the event of physical changes in the employee that may affect respirator fit.
- ☐ Employees are given the opportunity to select a different respirator facepiece, and be retested if their respirator fit is unacceptable to them.
- ☐ Fit tests are administered using QNFT or QLFT protocols.
- ☐ QLFT is only used to fit test either PAPRs, SCBAs or negative pressure APRs that must achieve a fit factor of 100 or less.
- ☐ QNFT is used in all situations where a negative pressure respirator is intended to protect workers from contaminant concentrations greater than 10 times the PEL.
- ☐ When QNFT is used to fit negative pressure respirators, a minimum fit factor

of 100 is achieved for tight-fitting half facepieces and 500 for full facepieces.

**For tight-fitting atmosphere-supplying respirators and powered air-purifying respirators:**

[ ] Fit tests are conducted in the negative pressure mode.

[ ] QLFT is achieved by temporarily converting the facepiece into a negative pressure respirator with appropriate filters, or by using an identical negative pressure APR.

[ ] QNFT is achieved by modifying the facepiece to allow for sampling inside the mask midway between the nose and mouth. If the facepiece is permanently converted during fit testing, the respirator is no longer approved for workplace use.